PATENT ABSTRACTS OF JAPAN

(11) Publication number: 04298302 A

(43) Date of publication of application: 22.10.92

(51) Int. CI

B28B 7/28

B29C 33/40

B29C 33/64

B29C 33/76

// B29K 21:00

B29L 23:00

(21) Application number: 03085791

(22) Date of filing: 27.03.91

(71) Applicant:

JAPAN SYNTHETIC RUBBER CO

LTD

(72) Inventor:

UESHIMA TOSHIFUMI UMEDA ITSUKI

MATSUMOTO HIRONORI

(54) MANDREL COATED WITH POLYORGANOSILOXANE

(57) Abstract:

PURPOSE: To obtain a mandrel at a low running cost in its production by coating the surface of rubber with a polyorganosiloxane composition having a predetermined mean polymerization degree represented by a specified formula and thereafter crosslinking the polyorganosiloxane composition to adhere to the surface of rubber by crosslinking.

CONSTITUTION: The surface of rubber is coated with a polyorganosiloxane composition having 20 to 10000 of a mean polymerization degree, which is represented by a mean composition formula $R_a SiO_{(4-a)/2}$ (a represents a positive number of not less than 1.900 and not more than

2.100; 0.01 to 25mol% of R has an unsaturated group and/or a phenylketone group as an essential component, or contains these groups and at least one kind of substituents selected from among a hydrogen atom, a hydroxyl group, an alkoxy group and the like; and the rest of R is a 1-15C hydrocarbon group (but an unsaturated group is excepted) and/or a component substituted by a fluorine group). After this coating, the polyorganosiloxane composition is crosslinked and allowed to adhere to the surface of the rubber by crosslinking to obtain a mandrel. By this method, less power is required when the mandrel thus obtained is withdrawn, and equipment for irradiation of light costs cheap and the irradiation for a short period of time may be sufficient enough.

COPYRIGHT: (C)1992,JPO&Japio